

**Catalog Number:** XT2VE3003BFF000XXX  
**UPC Number:** 88861448396  
**Status:** Active

Tmax XT Molded Circuit Breaker, Frame Size XT2 - to 125A, 600V (UL) / 160A (IEC), 690V ,  
Trip Type Thermal magnetic adjustable (TMD/TMA), 3 Poles

**North American Specifications (UNSPSC)**

|                  |                                                                                                                                                                       |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| UNSPSC           | 39121616 Molded case circuit breakers                                                                                                                                 |
| IGCC             | 4927 Molded case circuit breakers                                                                                                                                     |
| Brand Name       | ABB                                                                                                                                                                   |
| Sub Brand        | Tmax XT                                                                                                                                                               |
| Type             | Molded case circuit breaker                                                                                                                                           |
| Special Features | Feature high specific let-through current peak and energy limiting characteristics that allow the circuits and equipment on the load side to be sized in Optimum way. |
| Application      | Ideal solution for all distribution levels from the main low voltage switchboard to the subswitchboards in the installation                                           |
| Standard         | IEC only / use only for IEC specific needs                                                                                                                            |
| Frame            | XT2 - to 125A, 600V (UL) / 160A (IEC), 690V - Thermal magnetic and Electronic protection                                                                              |
| Trip Type        | Thermal magnetic adjustable (TMD/TMA)                                                                                                                                 |
| Number Of Poles  | 3 Poles                                                                                                                                                               |

**Packaging**

|                           |                |
|---------------------------|----------------|
| Outer Quantity            | 1              |
| Outer Dimensions (inches) | 8.19x5.71x5.12 |
| Weight Uom                | 2.65 lbs. Each |

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
www.tnb.com

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com