

Catalog Number: XT4NQ3100BFF1ALXXX
UPC Number: 88861447293
Status: Active

Tmax XT Molded Circuit Breaker, Frame Size XT4 - to 250A, 600V (UL) / 250A, 690V (IEC) ,
Trip Type Thermal magnetic adjustable (TMD/TMA), 3 Poles

North American Specifications (UNSPSC)

UNSPSC	39121616 Molded case circuit breakers
IGCC	4927 Molded case circuit breakers
Brand Name	ABB
Sub Brand	Tmax XT
Type	Molded case circuit breaker
Special Features	Feature high specific let-through current peak and energy limiting characteristics that allow the circuits and equipment on the load side to be sized in Optimum way.
Application	Ideal solution for all distribution levels from the main low voltage switchboard to the subswitchboards in the installation
Standard	UL 100% rated / IEC dual rated
Frame	XT4 - to 250A, 600V (UL) / 250A, 690V (IEC) - Thermal magnetic and Electronic protection
Trip Type	Thermal magnetic adjustable (TMD/TMA)
Number Of Poles	3 Poles

Packaging

Outer Quantity	1
Outer Dimensions (inches)	6.614x5.709x8.268
Weight Uom	6.83 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com