Representative Image

Catalog No. TL18415C

Description: MAIN LUG 150A 18CRT COMBO LD CENTER

UPC No 783164189896

Home > Load Centers > Load Centers

Main lug load centers can be used as a home's main panel or sub panel depending upon your preferences. All ABB load centers are rated up to 60 degree/75 degree centrigrade and is suitable for use with service entrance equipment when installed in accordance with electrical code. The TL18415C features space for 18, 1" breakers, 3 phases, a 150 A bus ampere rating, and a combination/flush enclosure.

Descriptors

Category	Load Centers
GO Schedule	R7

Specifications

# Branch Circuit 250A	18
1" Space	18
1/2" Space	0
Amperage	150 A
Circuit Breaker Style	Plug-In
Device type	Main Lug
Door	Yes
Enclosure	Indoor
Enclosure Type	Indoor, Combination
Factory Installed Ground Kit	No
Feed	Either
Input/Output Voltage	208Y/120V ac
Interrupting Capacity Rating	65
Load Center Type	Standard
NEMA Rating	NEMA 1
Phase	3 Phase
Service & Voltage	3 Phase, 4 Wire, 208Y/120V ac
Wires	4 Wire

Classifications

UL/CUL Listing	UL

Dimensions

Depth	3.7 in
Height	24.7 in
Weight	23.6 lb

Dimensions	
Width	14.0 in

Publications

Title	Publication No.	Publication Type
Section 1 BuyLog: Load centers, meter combos, single socket metering, and residential circuit breakers Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line.	DET1023	Application and Technical

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.