

Tray & VFD Cables

TR 600 S CY gray

UV and oil resistant 90°C shielded flexible tray cable
Type TC-ER, MTW, WTTC, and CSA approved



Marking for TR 600 S CY gray 93361604:

SAB NORTH AMERICA TR 600 S CY 93361604 16 AWG/ 4C (UL) TC-ER 90C DRY 75C WET 600V SUN RES DIR BUR OIL RES I/II OR WTTC 1000V OR

MTW "FLEXING" OR DP-1 OR AWM 2586 105°C CSA CIC-TC PVC/N 90°C DRY 75°C WET 600V -25°C SR FT4 OR AWM I/II A/B 90C 1000V FT4 RoHS CE

Construction:

Conductor:	bare copper strands class K (30 AWG multiple strands)
Insulation:	special formulated PVC/Nylon
Color code:	black conductors with consecutive white numbers; green/yellow ground from 3 conductors
Stranding:	in layers
Wrapping:	fleece tape
Shielding:	tinned copper braiding (85% coverage)
Jacket material:	special oil resistant pressure extruded PVC
Jacket color:	gray (RAL 7000)

Outstanding features:

- flexible stranding for easy installation
- oil resistant meeting UL Oil Res I and II
- NFPA 79 for Industrial Machinery
- UL TC-ER (exposed run)
- CSA approved for TC
- Submersible pump (14 AWG ≥ 3 thru 7 cond.)
- WTTC: Wind Turbine tray cable
- Class 1 Div 2 per NEC Article 501.4 (B)

Technical data:

Voltage:	UL-AWM / (UL) / CSA: 600 V (UL) WTTC: 1000 V
Testing voltage:	2500 V
Min. bending radius: <i>fixed installation:</i> <i>free movement:</i>	6 x O.D. 8 x O.D.
Temperature range: <i>static:</i>	UL -AWM (UL) / CSA: up to +105°C up to +90°C -40°C
Burning characteristics:	(UL) FT4 and CSA FT1, FT2, FT4
Oil resistance I & II:	yes
Sunlight resistance:	yes
Exposed runs:	yes
Cold bend test:	-40°C
Direct burial:	yes
Machinery area:	yes
Approvals:	UL TC-ER, UL MTW, UL WTTC, UR AWM, CSA CIC-TC, CSA CIC, CSA AWM, CE, RoHS
Absence of harmful substances:	acc. to RoHS directive of the European Union see page O/30

item no.	no. of conductors incl. ground	nominal outer-ø inch	mm	cable weight ≈lbs/mft
▶ 18 AWG				
93361803	3	0.324	8.2	71
93361804	4	0.348	8.8	85
93361805	5	0.373	9.5	95
93361807	7	0.400	10.2	120
93361809	9	0.455	11.6	149
93361812	12	0.504	12.8	185
93361818	18	0.617	15.7	270
93361825	25	0.710	18.0	365
▶ 16 AWG				
93361603	3	0.345	8.8	83
93361604	4	0.372	9.4	100
93361605	5	0.400	10.2	116
93361607	7	0.430	10.9	145
93361609	9	0.492	12.5	187
93361612	12	0.579	14.7	245
93361618	18	0.664	16.9	335
93361625	25	0.770	19.6	445

item no.	no. of conductors incl. ground	nominal outer-ø inch	mm	cable weight ≈lbs/mft
▶ 14 AWG				
93361403	3	0.388	9.9	108
93361404	4	0.420	10.7	131
93361405	5	0.454	11.5	155
93361407	7	0.490	12.4	190
93361412	12	0.662	16.8	350
93361418	18	0.764	19.4	482
93361425	25	0.924	23.5	701
▶ 12 AWG				
93361203	3	0.427	10.8	145
93361204	4	0.464	11.8	178
93361205	5	0.506	12.9	210
▶ 10 AWG				
93361003	3	0.562	14.3	190
93361004	4	0.568	14.4	250
93361005	5	0.643	16.3	350
93361007	7	0.695	17.7	408

item no.	no. of conductors incl. ground	nominal outer-ø inch	mm	cable weight ≈lbs/mft
▶ 8 AWG				
93360804	4	0.759	19.3	447
▶ 6 AWG				
93360604	4	0.915	23.2	672
▶ 4 AWG				
93360404	4	1.097	27.9	993
▶ 2 AWG				
93360204	4	1.271	32.3	1455

Other dimensions and colors are available on request