



Product designation				Auxiliary contact
Product type designation				BFX10
Contact characteristics				
Number of poles	Nr.			2
Rated insulation voltage U_i IEC/EN	V			690
Rated impulse withstand voltage U_{imp}	kV			6
IEC Conventional free air thermal current I_{th}	A			10
Tightening torque for terminals	min	Nm	0.8	
	max	Nm	1	
	min	lbin	7	
	max	lbin	9	
Max number of wires simultaneously connectable	Nr.			2
Conductor section	AWG/Kcmil			
		max	14	
	Flexible w/o lug conductor section			
		min	mm ²	0.75
		max	mm ²	2.5
	Flexible c/w lug conductor section			
		min	mm ²	0.75
		max	mm ²	2.5
	Flexible with insulated spade lug conductor section			
		min	mm ²	0.75
	max	mm ²	2.5	
Mechanical features				
Operating position	normal		On vertical plane	
	allowable		Any	
Fixing				Front centre mounting
Weight				g 48
Terminals screw				Screw
Auxiliary contact characteristics				
Type of contact				2NO
Thermal current I_{th}	A			10
IEC/EN 60947-5-1 designation				A600 - Q600
Operating current AC15	230V	A	3	
	400V	A	1.9	
	500V	A	1.4	
Operating current DC13	24V	A	3	
	48V	A	1.5	
	60V	A	1.2	

110V	A	0.6
125V	A	0.55
220V	A	0.27
600V	A	0.1

Electrical characteristics

Conductivity			5V 10 mA
UL/CSA and IEC/EN 60947-5-1 designation			A600 Q600

Operating current AC15

120V	A	6
240V	A	3
480V	A	1.5
600V	A	1.2

Operating current DC13

12V	A	10
250V	A	0.27
440V	A	0.15
500V	A	0.13

UL technical data

Rated operational voltage AC (UL)	V	600
-----------------------------------	---	-----

Ambient conditions

Temperature

Operating temperature

min	°C	-50
max	°C	+70


Storage temperature

min	°C	-60
max	°C	+80


Max altitude

m	3000
---	------

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 60947-1

CSA C22.2 n° 60947-5-1

IEC/EN 60947-1

IEC/EN 60947-5-1

UL 60947-1

UL 60947-5-1

Certificates

CCC

cULus

EAC

ETIM classification

ETIM 8.0

EC000041 -
Auxiliary contact
block