



Product designation
Product type designation

Power contactor
BFK95

Contact characteristics


Number of poles	Nr.	3
Rated insulation voltage U_i IEC/EN	V	690
Rated impulse withstand voltage U_{imp}	kV	8
Operational frequency	min Hz	25
	max Hz	400
IEC Conventional free air thermal current I_{th}	A	140
Rated operational power AC-6b ($T \leq 40^\circ C$)	230V kvar	34
	400V kvar	60
	440...480V kvar	75
	690V kvar	80
Short-time allowable current for 10s (IEC/EN60947-1)	A	760
Protection fuse	gG (IEC)	A 125
Making capacity (RMS value)	A	1200
Breaking capacity at voltage	440V A	1100
	500V A	775
	690V A	745
Resistance per pole (average value)	m Ω	0.45
Power dissipation per pole (average value)	I_{th} W	8.8
Tightening torque for terminals	min Nm	6
	max Nm	7
	min lbin	4.4
	max lbin	5.2
Tightening torque for coil terminal	min Nm	0.8
	max Nm	1
	min lbin	0.59
	max lbin	0.74
Max number of wires simultaneously connectable	Nr.	2
Conductor section	AWG/Kcmil	
	max	2/0
Flexible w/o lug conductor section	min mm ²	1.5
	max mm ²	70
Flexible c/w lug conductor section	min mm ²	1.5

	max	mm ²	70
Power terminal protection according to IEC/EN 60529			IP20 front
Mechanical features			
Operating position	normal allowable		Vertical plan ±30°
Fixing			Screw / DIN rail 35mm
Weight		g	2095
Operations			
Mechanical life		cycles	15000000
Electrical life		cycles	400000
Safety related data			
Performance level B10d according to EN/ISO 13489-1			
	rated load mechanical load	cycles	400000
		cycles	15000000
EMC compatibility			yes
AC coil operating			
Rated AC voltage at 60Hz		V	48
AC operating voltage			
	of 60Hz coil powered at 60Hz		
	pick-up	min	%Us 80
		max	%Us 110
	drop-out	min	%Us 20
		max	%Us 55
Dissipation at holding ≤20°C 50Hz		W	6.5
Max cycles frequency			
Mechanical operation		cycles/h	1500
Operating times			
Average time for Us control in AC			
	Closing NO	min	ms 16
		max	ms 32
	Opening NO	min	ms 9
		max	ms 24
UL technical data			
Rated operational voltage AC (UL)		V	600
General USE			
	Contactor		
	AC current	A	140
Ambient conditions			
Temperature			
	Operating temperature	min	°C -50
		max	°C 70
	Storage temperature	min	°C -60
		max	°C 80
Max altitude		m	3000
Resistance & Protection			


Pollution degree

3

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 60947-1

CSA C22.2 n° 60947-4-1

IEC/EN/BS 60947-1

IEC/EN/BS 60947-4-1

UL 60947-1

UL 60947-4-1

Certificates

CCC

cULus

ETIM classification

ETIM 8.0

EC001079 -
Capacitor
contactor

