

|                                                        |          |    |      |                                         |
|--------------------------------------------------------|----------|----|------|-----------------------------------------|
| Product designation                                    |          |    |      | Rotary cam switches                     |
| Product type designation                               |          |    |      | GX32                                    |
| General characteristics                                |          |    |      |                                         |
| Switching diagram                                      |          |    |      | 54 - Changeover switch without 0 1 pole |
| N° of elements                                         |          |    |      | 1                                       |
| Mounting form                                          |          |    |      | U - Front mounting with black handle    |
| Contact characteristics                                |          |    |      |                                         |
| Rated insulation voltage Ui                            |          |    |      |                                         |
|                                                        | IEC/EN   | V  | 690  |                                         |
|                                                        | UL/CSA   | V  | 600  |                                         |
| Rated impulse withstand voltage Uimp                   |          |    |      | kV 6                                    |
| Conventional free air thermal current Ith              |          |    |      |                                         |
|                                                        | IEC/EN   | A  | 32   |                                         |
|                                                        | UL/CSA   | A  | 32   |                                         |
| Rated operational voltage                              |          |    |      | V 440                                   |
| Rated operational impulse voltage                      |          |    |      | kV 4                                    |
| Maximum fuse size for short-circuit protection In (gG) |          |    |      |                                         |
|                                                        | 10kA     | A  | 35   |                                         |
|                                                        | 15kA     | A  | 35   |                                         |
|                                                        | 25kA     | A  | 35   |                                         |
| Rated short time current Icw                           |          |    |      |                                         |
|                                                        | 1s       | kA | 1000 |                                         |
| Conductivity                                           |          |    |      | 10/5 mA/V                               |
| Operational current Ie IEC/EN                          |          |    |      |                                         |
| AC1/AC21A                                              |          |    |      |                                         |
|                                                        |          | A  | 32   |                                         |
| AC15                                                   |          |    |      |                                         |
|                                                        | 110V     | A  | 25   |                                         |
|                                                        | 220/230V | A  | 20   |                                         |
|                                                        | 380/400V | A  | 10   |                                         |
|                                                        | 660/690V | A  | 2    |                                         |
| Rated operational power in AC                          |          |    |      |                                         |
| Three-phase AC-3                                       |          |    |      |                                         |
|                                                        | 220/230V | kW | 7.5  |                                         |
|                                                        | 380/440V | kW | 11   |                                         |
|                                                        | 500/690V | kW | 11   |                                         |
| Single-phase AC-3                                      |          |    |      |                                         |
|                                                        | 110V     | kW | 1.8  |                                         |
|                                                        | 220/230V | kW | 3.5  |                                         |
|                                                        | 380/440V | kW | 5.5  |                                         |
| Three-phase AC23A                                      |          |    |      |                                         |
|                                                        | 220/230V | kW | 8    |                                         |
|                                                        | 380/440V | kW | 15   |                                         |
|                                                        | 500/690V | kW | 15   |                                         |
| Single-phase AC23A                                     |          |    |      |                                         |
|                                                        | 110V     | kW | 2.2  |                                         |
|                                                        | 220/230V | kW | 3.5  |                                         |
|                                                        | 380/440V | kW | 6    |                                         |

Rated operational current in DC

DC21A

|      |   |      |
|------|---|------|
| 48V  | A | 32   |
| 60V  | A | 32   |
| 110V | A | 5    |
| 220V | A | 0.8  |
| 440V | A | 0.25 |

DC23A (poles in series)

|      |   |        |
|------|---|--------|
| 24V  | A | 32 (1) |
| 48V  | A | 32 (2) |
| 60V  | A | 32 (3) |
| 110V | A | 15 (3) |
| 220V | A | 12 (4) |

DC13

|      |   |      |
|------|---|------|
| 24V  | A | 32   |
| 48V  | A | 25   |
| 60V  | A | 14   |
| 110V | A | 3    |
| 220V | A | 0.5  |
| 440V | A | 0.15 |

Power dissipation

W 1.6

#### Mechanical features

Terminals screw

M4

Tightening torque for terminals max

Nm 1.2

Conductor size

AWG - Rigid cable

|     |     |    |
|-----|-----|----|
| min | AWG | 16 |
| Max | AWG | 8  |

AWG - Flexible cable

|     |     |    |
|-----|-----|----|
| min | AWG | 16 |
| Max | AWG | 10 |

Conductor size (IEC) - Flexible cable

|     |                 |     |
|-----|-----------------|-----|
| min | mm <sup>2</sup> | 1.5 |
| Max | mm <sup>2</sup> | 6   |

Conductor size (IEC) - Rigid cable

|     |                 |     |
|-----|-----------------|-----|
| min | mm <sup>2</sup> | 1.5 |
| Max | mm <sup>2</sup> | 10  |

Mechanical life

cycles 1X10<sup>6</sup>

#### UL technical data

Motor power for direct-on-line control

for three-phase motor

|      |    |     |
|------|----|-----|
| 120V | HP | 3   |
| 240V | HP | 7.5 |
| 480V | HP | 15  |
| 600V | HP | 15  |

for single-phase motor

|      |    |     |
|------|----|-----|
| 120V | HP | 1.5 |
| 240V | HP | 3   |

#### Ambient conditions

Temperature

Operating temperature

|     |    |     |
|-----|----|-----|
| min | °C | -25 |
| max | °C | +55 |


Storage temperature

|     |    |     |
|-----|----|-----|
| min | °C | -40 |
| max | °C | +70 |

### Resistance & Protection


|                     |      |
|---------------------|------|
| Frontal IP degree   | IP65 |
| Terminals IP degree | IP20 |

### Dimensions



| Series | Dimensions |      |     |     |      |    |    | L Number of elements |      |    |      |    |      |     |       |     |       |     |       |
|--------|------------|------|-----|-----|------|----|----|----------------------|------|----|------|----|------|-----|-------|-----|-------|-----|-------|
|        | □A         | C    | ØD1 | ØD2 | E    | □K | □N | 1                    | 2    | 3  | 4    | 5  | 6    | 7   | 8     | 9   | 10    | 11  | 12    |
| GX16   | 48         | 39.5 | 12  | 5   | 26.5 | 36 | 6  | 43                   | 51.5 | 60 | 68.5 | 77 | 85.5 | 94  | 102.5 | 111 | 119.5 | 128 | 136.5 |
| GX20   | 48         | 39.5 | 12  | 5   | 26.5 | 36 | 6  | 43                   | 51.5 | 60 | 68.5 | 77 | 85.5 | 94  | 102.5 | 111 | 119.5 | 128 | 136.5 |
| GX32   | 65         | 53   | 14  | 5   | 34.5 | 48 | 7  | 51                   | 63   | 75 | 85   | 99 | 111  | 123 | 135   | 147 | 159   | 171 | 183   |
| GX40   | 65         | 53   | 14  | 5   | 34.5 | 48 | 7  | 51                   | 63   | 75 | 85   | 99 | 111  | 123 | 135   | 147 | 159   | 171 | 183   |

### Wiring diagrams



### Certifications and compliance

#### Compliance

CSA C22.2 n° 14

IEC/EN/BS 60947-1

IEC/EN/BS 60947-3

IEC/EN/BS 60947-5-1

IEC/EN/BS 61058-1

UL60947-4-1

#### Certificates

cULus

EAC

### ETIM classification

ETIM 8.0

EC001105 - Off-load switch