

|                                                        |                                                                          |                  |                     |
|--------------------------------------------------------|--------------------------------------------------------------------------|------------------|---------------------|
| Product designation                                    | Rotary cam switches                                                      |                  |                     |
| Product type designation                               | GX16                                                                     |                  |                     |
| General characteristics                                |                                                                          |                  |                     |
| Switching diagram                                      | 85 - Multi-step 1-2-3-4-6 1 pole                                         |                  |                     |
| N° of elements                                         | 3                                                                        |                  |                     |
| Mounting form                                          | O48 - Modular service cover for 35mm din rail mounting with black handle |                  |                     |
| Contact characteristics                                |                                                                          |                  |                     |
| Rated insulation voltage Ui                            | IEC/EN<br>UL/CSA                                                         | V<br>V           | 690<br>600          |
| Rated impulse withstand voltage Uimp                   |                                                                          | kV               | 6                   |
| Conventional free air thermal current Ith              | IEC/EN<br>UL/CSA                                                         | A<br>A           | 16<br>12            |
| Rated operational voltage                              |                                                                          | V                | 440                 |
| Rated operational impulse voltage                      |                                                                          | kV               | 4                   |
| Maximum fuse size for short-circuit protection In (gG) | 10kA<br>15kA<br>25kA                                                     | A<br>A<br>A      | 16<br>16<br>16      |
| Rated short time current Icw                           | 1s                                                                       | kA               | 250                 |
| Conductivity                                           | 10/5 mA/V                                                                |                  |                     |
| Operational current Ie IEC/EN                          |                                                                          |                  |                     |
| AC1/AC21A                                              |                                                                          | A                | 16                  |
| AC15                                                   | 110V<br>220/230V<br>380/400V<br>660/690V                                 | A<br>A<br>A<br>A | 10<br>8<br>4<br>1.5 |
| Rated operational power in AC                          |                                                                          |                  |                     |
| Three-phase AC-3                                       | 220/230V<br>380/440V<br>500/690V                                         | kW<br>kW<br>kW   | 3.5<br>4.5<br>5.5   |
| Single-phase AC-3                                      | 110V<br>220/230V<br>380/440V                                             | kW<br>kW<br>kW   | 0.55<br>1.5<br>2.2  |
| Three-phase AC23A                                      | 220/230V<br>380/440V<br>500/690V                                         | kW<br>kW<br>kW   | 3.7<br>6.5<br>7.5   |
| Single-phase AC23A                                     | 110V<br>220/230V                                                         | kW<br>kW         | 0.75<br>1.8         |

|                                        |  |          |                 |                   |
|----------------------------------------|--|----------|-----------------|-------------------|
|                                        |  | 380/440V | kW              | 3                 |
| Rated operational current in DC        |  |          |                 |                   |
| DC21A                                  |  |          |                 |                   |
|                                        |  | 48V      | A               | 16                |
|                                        |  | 60V      | A               | 16                |
|                                        |  | 110V     | A               | 4                 |
|                                        |  | 220V     | A               | 0.6               |
|                                        |  | 440V     | A               | 0.25              |
| DC23A (poles in series)                |  |          |                 |                   |
|                                        |  | 24V      | A               | 16 (1)            |
|                                        |  | 48V      | A               | 16 (2)            |
|                                        |  | 60V      | A               | 16 (3)            |
|                                        |  | 110V     | A               | 10 (3)            |
|                                        |  | 220V     | A               | 7 (4)             |
| DC13                                   |  |          |                 |                   |
|                                        |  | 24V      | A               | 16                |
|                                        |  | 48V      | A               | 14                |
|                                        |  | 60V      | A               | 10                |
|                                        |  | 110V     | A               | 1                 |
|                                        |  | 220V     | A               | 0.4               |
|                                        |  | 440V     | A               | 0.15              |
| Power dissipation                      |  |          | W               | 0.6               |
| Mechanical features                    |  |          |                 |                   |
| Terminals screw                        |  |          |                 | 3M                |
| Tightening torque for terminals max    |  |          | Nm              | 0.5               |
| Conductor size                         |  |          |                 |                   |
| AWG - Rigid cable                      |  |          |                 |                   |
|                                        |  | min      | AWG             | 20                |
|                                        |  | Max      | AWG             | 12                |
| AWG - Flexible cable                   |  |          |                 |                   |
|                                        |  | min      | AWG             | 20                |
|                                        |  | Max      | AWG             | 12                |
| Conductor size (IEC) - Flexible cable  |  |          |                 |                   |
|                                        |  | min      | mm <sup>2</sup> | 0.5               |
|                                        |  | Max      | mm <sup>2</sup> | 2.5               |
| Conductor size (IEC) - Rigid cable     |  |          |                 |                   |
|                                        |  | min      | mm <sup>2</sup> | 0.5               |
|                                        |  | Max      | mm <sup>2</sup> | 2.5               |
| Mechanical life                        |  |          | cycles          | 1X10 <sup>6</sup> |
| UL technical data                      |  |          |                 |                   |
| Motor power for direct-on-line control |  |          |                 |                   |
| for three-phase motor                  |  |          |                 |                   |
|                                        |  | 120V     | HP              | 1.5               |
|                                        |  | 240V     | HP              | 3                 |
|                                        |  | 480V     | HP              | 5                 |
|                                        |  | 600V     | HP              | 5                 |
| for single-phase motor                 |  |          |                 |                   |
|                                        |  | 120V     | HP              | 0.75              |
|                                        |  | 240V     | HP              | 1                 |
| Ambient conditions                     |  |          |                 |                   |
| Temperature                            |  |          |                 |                   |
| Operating temperature                  |  |          |                 |                   |
|                                        |  | min      | °C              | -25               |
|                                        |  | max      | °C              | +55               |

Storage temperature

|     |    |     |
|-----|----|-----|
| min | °C | -40 |
| max | °C | +70 |


## Resistance & Protection

Frontal IP degree IP65

Terminals IP degree IP20

## Dimensions

## Wiring diagrams



|   |   |   |   |   |   |
|---|---|---|---|---|---|
| 1 | X |   |   |   |   |
| 2 |   |   | X |   |   |
| 3 |   |   |   |   | X |
| 4 |   | X |   |   |   |
| 5 |   |   |   | X |   |
| 6 |   |   |   |   | X |

85

## Certifications and compliance

### Compliance

CSA C22.2 n° 14

IEC/EN/BS 60947-1

IEC/EN/BS 60947-3

IEC/EN/BS 60947-5-1

IEC/EN/BS 61058-1

UL60947-4-1

### Certificates

cULus

EAC

## ETIM classification

ETIM 8.0

EC001029 -  
Selector switch,  
complete